

Orange Peel Grabs



Gusella Bakker SHM 135 OPG

CAPACITY (LITRES)	SWL(T)	CONNECTOR	DESCRIPTION
130 Litres	4 T	Deployed via MacArtney winch and operated through the ROV Hot-Stab and Dynaset water circuit.	Smaller 130 Litres orange peel grab, hard wearing points on each tooth with replaceable teeth.



Gusella Bakker SCE605 OPG

CAPACITY (LITRES)	SWL(T)	CONNECTOR	DESCRIPTION
600 Litres	7 T	Connected by Hydraulic Swivel Ring Rotator	Five tooth larger orange peel grab. Replaceable teeth, connected by a hydraulic swivel ring rotator connector.



Mechanical Services Custom OPG

CAPACITY (LITRES)	SWL(T)	CONNECTOR	DESCRIPTION
500 Litres	10 T	Deployed via MacArtney winch and operated through the ROV Hot-Stab and Dynaset water circuit.	Custom made updated orange peel grab from Mechanical Services, deployed by winch and connected to ROV via hot-stab system.



NOTE: Package configuration subject to change and will be customised for individual projects

1st Floor Tudor House
Le Bordage, St Peter Port
GY1 1DB, Guernsey

E: operations@magellan.gg
www.magellan.gg